



LEAP

CHARGING STATION (1)
 PORTABLE CHARGERS (8)
 REMOVABLE (2) PRONG PLUG FOR ALL SOCKET TYPES

POWER STATION

SPECIFICATION

Material : ABS plastic
 Color :Black / White
 Dimension (power station) : 276*82*38mm
 Weight (power station):420g
 Input voltage: AC 100-240V
 Input frequency: 47-63HZ
 Input surge: 120V@30A 230V@50A
 Static power (MW): <0.5W
 Start me: ≤ 1S
 Voltage regular on: ≤ 0.5%
 Output voltage: 5V
 Output voltage range: 5V± 5%
 Output current: 12000MA
 Output power: 60W

SAFETY PROTECTION

Overload protec on: 105%-150% rated power
 Insula on strength: >1500VAC / one minute
 Insula on resistance: P-S>50M ohm at 500V DC
 Storage temperature: -40C ~ 85C, humidity: 10% - 95%
 Working temperature: -20C ~ +45C, humidity: 20% - 90%
 Cooling mothed: natural cooling

PORTABLE CHARGER

Material : ABS plastic
 Color :Black / White
 Dimension(power bank): 102*42*22mm
 Weight (1 power bank):81g
 Battery type: A grade Lithium-ion battery
 Capacity: 2600MAH, 3.7V (LG or Samsung)
 Input: 5V/1.5A (Max)
 Output : 5V/2.1A (Max)
 Overpower protection: 5V/2300MA
 Static current: ≤ 100UA
 Floating voltage: 5V±5%
 Output efficiency: >86%
 Charging me: 2 hours
 Set-up me: 2 seconds

Overload protec on: 105%-150% rated power
 Short-circuit protection: automatic activation
 Overcharge protection: 4.2V±0.05V
 Over discharge protection: 3.0V±0.1V